

HEAT INPUT POWER

BTU/hr 10.000 – 40.000

TOTAL HEAT OUTPUT

BTU/hr 8.500 – 35.000

Ravelli®
il fuoco intelligente

FRANCESCA

200lb – 35 lb Pellet



Bordeaux
Bordeaux



Black
Noir



White
Blanc

- Efficiency (based on LHV) 85%
- Rounded cast iron front part
- Cast iron firepot
- Wide view of the flames
- Extractable ash pan
- Top exhaust tube
- Sliding structure for Easy Inspection

Ravelli®

il fuoco intelligente



RAVELLI DYNAMIC SYSTEM

RDS is Ravelli's innovative system for automatically regulating combustion parameters and ensuring maximum efficiency and safety from your stove.



FIREX 600

All Ravelli's products have a combustion chamber made from FIREX 600, a vermiculite based material developed by Ravelli after long and extensive research.



GLASS CLEANING SYSTEM

A supplementary air duct over the door creates an air cushion between the flame and the ceramic glass, to keep the door glass clean for many hours of burning.



ECO-START QUICK IGNITION SYSTEM

The Eco-Start ignition system ensures that the stove lights quickly and safely. By reducing the time for which the ignition element has to operate, the system dramatically extends its life.



TIMER-THERMOSTAT

A timer-thermostat lets you program in two ignition times and two finish times so that you can make optimal daily and weekly use of the stove.



CAST MAJOLICA BODY

The attractively shaped stove body is in colourful majolica for a high prestige finish and excellent heat diffusion.



ASH PAN

A functional and easily accessible ash pan collects all the burned out ash.



STAINLESS STEEL HEAT EXCHANGER

A stainless steel heat exchanger means increased fire resistance and reduced wear.

The manufacturer assumes no responsibility for any errors or inaccuracies in the content of this catalog and reserves the right to modify its products at any time and without prior notice, and make changes considered appropriate for either technical or commercial reasons.

www.ravelligroup.it

HEAT INPUT POWER

BTU/hr 10.000- 40.000

TOTAL HEAT OUTPUT

BTU/hr 8.500- 35.000

FRANCESCA

200lb - 35 lb Pellet

FIREX
CLEAR
INOX
ECO START
TIMER
ASH
RDS
MAJOLICA



HEAT INPUT	BTU/hr	10,000 – 40,000
HEAT OUTPUT	BTU/hr	8,500 – 35,000
FEED RATE	lb/hr	1.5 – 4.41
EFFICIENCY (based on LHV)	%	87
VENTING SIZE	Ø mm	80/3.15
HOPPER CAPACITY	lb	35
BURN TIME	hr	7.5 – 22
NET WEIGHT	lb	200

